

ENERpro-LFP48300

Battery Energy Storage Residential|Self-Heating|51.2V 300Ah 15.3kWh



The state-of-the-art LiFePo4 battery offers a reliable and efficient energy storage solution. Whether you're powering a home or a commercial building, EGbatt system provides unmatched flexibility & performance.

Product Highlights:

Capacity: 15.3kWh

Battery Type: Grade A brand new

Lithium Iron Phosphate battery


Mobility: Easy to move with Fuma

wheels

Application: Perfect for both residential

and commercial use

Expandable: Scale your energy storage from 15kWh to an impressive 200kWh



ELECTRICAL SPECIFICATIONS	
Nominal voltage	51.2V
Nominal capacity	300Ah
Nominal energy	15.3kWh
Operating voltage range	44.8V~56.0V
Charge voltage	56.8V
Float voltage	54.6V
Recommended charge current	100A
Max. charge current	200A
Recommended discharge current	150A
Max. discharge current	200A
Communication	RS485/CAN
Peak discharge current	240A/15S 360A/1S
IP rating	IP54
Cycle life @ 80% DOD	≥9500cycles
Design life	15Years
Operation temperature	Min:-20°C(- 4°F)Max:50°C(122°F)
Storage temperature	Min:-20°C(- 4°F)Max:45°C(113°F)

MECHANICAL SPECIFICATIONS	
Dimensions (H×W×D)	850(with wheels)*453*240mm34.4(with wheels)*17.7*9.5inch
Weight	135kgs
Cell(s)	16S1P
Electrolyte	LiFePO4
Certification	CE/IEC62619/UN38.3 UL1973/UL9540 pending
Warranty	10Years

Tel: 086-18676987799 Web: www.egbatt.com/

Email: tony@egbatt.com



Long term Service Life

EGbatt LFP48300 rated more than 9500 cycles, 10 years factory warranty. 15 years service life, providing long-term energy for your home



FUMAWHEELS AND WALL MOUNTED FIXATION

Four concealed heavy-duty Fuma wheels facilitate movement of the battery without detracting from the elegant design. An anti-tipping mount on the back anchors the battery to the wall.



BATTERY MAINTENACE AND INSPECTION PORT

LFP4300 Equipped Touch screen, Can easy select communication protocols by built in RS485/ CAN bus ports, the most important, which can monitor the equipment information at any time on the mobile phone or PC



ALL POLE PROTECTION

Built-in Robust 200A BMS. All-pole, dual protection through fuse (negative terminal) and micro circuit breaker (positive terminal).



INTELLIGENT BALANCING

A double equilibrium approach enhances cell balancing efficiency by calculating capacity differences between battery cells using charging-process data and extending the balancing time. This method significantly improves efficiency and reliability compared to standard passive and active balancing modes.





ON-GRID EPS



VIRTUAL POWER PLANT (VPP)



TIME OF USE MANAGEMENT



MICRO-GRIDS



DIESEL OFF-SET



PEAK SHAVING



ENERGY SHIFTING

